



## FC39V/2

Combined refrigerator freezers

+2° + 12°/ - 10° - 30°C from 200/100 to 700/700 lt > Capacity 300 lt



### FC39V/2 Model

Refrigerator compartment: 200LT - Freezer compartment: 100LT

### Structure

External structure in hot-dip galvanized steel, anti-corrosion treated and PVC film coated.  
Scotch-brite stainless steel internal structure.

### Insulation

60 mm of insulation obtained by injection of high density ecological polyurethane CFC-free foam for excellent product preservation and best energy saving

### **Door**

Self-closing glass door (double insulating - low emissivity glass) for refrigerator compartment and self-closing solid door for freezer compartment. Folding magnetic gasket on four sides for perfect closing. Right hand opening or left hand on request. Locks with key.

### **Light**

LED light (energy saving up to 70%, ecological) with automatic switch at door opening in refrigerator compartment. Manual switch on control panel.

### **Internal fittings**

3 scotch-brite stainless steel shelves, removable and adjustable in height in refrigerator compartment.

2 scotch-brite stainless steel drawers with telescopic ball-bearing slides and Plexiglas frontal side in freezer compartment.

### **Temperature range**

Refrigerator compartment: between +2°C and +12°C. Factory preset to +4°C.

Freezer compartment: between -10°C and -30°C. Factory preset to -25°C.

Digital adjustable setting with an increment of 0.1°C.

### **Refrigeration system**

Two completely sealed, silent and highly efficient hermetic compressors and ventilated air condensers (suitable also for tropical countries). Forced-air cooling system in refrigerator compartment conceived to achieve maximum temperature uniformity and stability even in case of frequent door openings. Evaporator fan shuts off during door openings. Static evaporator in freezer compartment.

CFC-free R452a refrigerant gas. CFC/HCFC-free R290 refrigerant gas for European countries.

### **Defrosting**

Fully automatic defrosting cycle and auto-evaporation of condensed water in refrigerator compartment. Manual defrost in freezer compartment.

### **Capacity**

Refrigerator compartment: 200LT

Freezer compartment: 100LT

### **Voltage**

230V/50 Hz (on request 230V/60 Hz, 115V/60 Hz)

### **Absorption**

Refrigerator compartment: 240 Watt

Freezer compartment: 240 Watt

## **Gas**

CFC-free R452a refrigerant gas. CFC/HCFC-free R290 refrigerant gas for European countries.

## **Control panel and alarms**

Microprocessor control panel with colour 4.3" LCD touch screen and 4 keys. Display with 0.1°C resolution. Temperature monitoring detected by two independent PT1000 probes. Real time temperature graph (to be activated by end user). Optional humidity sensor. RS 232/RS 485 port. Digital calibration of probes. Visual and audible alarms of high and low temperature (by means of independent probe), open door, condenser efficiency, damaged probes, power failure at electricity recovery, power failure with recording of data and alarms (by means of optional back-up battery), damaged or flat battery. Memory of latest alarms visible on display.

## **Data logger**

To record temperatures and alarms in refrigerator and freezer compartments. Download data on USB pen drive.

## **Standard**

- 3 shelves in refrigerator compartment
- 2 drawers in freezer compartment
- Four one way wheels with stabilizing adjustable feet
- 2 locks with key
- Power cord with Schüko type plug (or British plug on request)
- Protection fuses (on power switch and electronic mainboard)
- RFI filter
- Password protected power switch and settings
- Electronic control panel with alarm system
- Remote contact (dry, volt-free) for alarm
- Data logger with USB port to download readings and data
- Memory of latest alarms visible on screen
- Power failure at electricity recovery

## **Optional accessories**

- Sliding drawers (up to 3) in scotch-brite stainless steel, with see-through frontal side and telescopic ball-bearings slides in refrigerator compartment
- Internal dividers for drawers
- Additional shelf
- Smooth shelf with borders
- Castors with two frontal brakes
- Weekly temperature chart recorder working with 1,5 V battery, equipped with 52 disks and a pen
- Back-up battery supplying energy to control panel in order to generate alarms in case of power failure

- GSM module to send SMS alarm messages to mobile phones, showing date, time, cabinet temperature and type of alarm
- LAN Port to connect the appliance via ethernet on PC to monitor correct functioning
- Safety thermostat in refrigerator compartment
- Digital humidity sensor
- Test hole (Ø 25 mm)
- Electric digital key lock
- Power supply 115V/60Hz

**External dimensions and unit net weight**

600x600x1970 (wxdxh-mm)-kg. 131

**Dimensions of packaging and shipping weight**

-carton box on pallet: 700x700x2200 (wxdxh-mm)-kg. 141

-wooden crate (option on request): 960x840x2260 (wxdxh-mm)-kg. 207

**Equipment in accordance with:**

Low voltage Directive 2014/35/UE, Electromagnetic Compatibility Directive 2014/30/UE

*Should it be necessary or useful without undermining any model essential features, technical and stylistic characteristics are subject to be changed without manufacturer's previous notice. The picture doesn't necessarily show the product in its standard version.*

**©Copyright FRI.MED. S.r.l.**

Strada Fontaneto 44 10023 Chieri (TO) - Italy

p.IVA /C.F. 07356760012